



## Temperature transmitter

### NTM 300

- RTD, TC, Ohm or mV input
- HART protocol, FDT and DTM support
- High accuracy
- Excellent EMC performance
- 1500V AC dielectric strength
- Configurable input types and ranges



#### Technical data

Power supply:	12 V DC~28 V DC (Reverse power protection)
Input signal:	K, E, S, B, J, T, R, N, etc Pt100, Cu100, Cu50, BA1, BA2, etc millivolt signal (-10mV~120mV) resistance signal (0~400 )
Line resistance:	20 per line (RTD)
Output signal:	4~20mA
Load resistance:	$RL \leq [(U-12)/0.022]$ ; U is loop powered volts

Range and Conversion accuracy list (25°C±2°C, not contain cold junction compensation)

Type	Range	Min.span/Accuracy	
K	-200°C~+1372°C	<300°C, ±0.3°C	300°C, ±0.1% F.S.
E	-100°C~+1000°C	<300°C, ±0.3°C	300°C, ±0.1% F.S.
J	-100°C~+1200°C	<300°C, ±0.3°C	300°C, ±0.1% F.S.
N	-200°C~+1300°C	<300°C, ±0.3°C	300°C, ±0.1% F.S.
S	-50°C~+1768°C	<500°C, ±0.5°C	500°C, ±0.1% F.S.
R	-50°C~+1768°C	<500°C, ±0.5°C	500°C, ±0.1% F.S.
T	-20°C~+400°C	<300°C, ±0.3°C	300°C, ±0.1% F.S.
B	+400°C~+1820°C	<500°C, ±0.5°C	500°C, ±0.1% F.S.
Pt100	-200°C~+850°C	<100°C, ±0.1°C	100°C, ±0.1% F.S.
Cu50	-50°C~+150°C	<100°C, ±0.1°C	100°C, ±0.1% F.S.
Cu100	-50°C~+150°C	<100°C, ±0.1°C	100°C, ±0.1% F.S.
mv	-10mV~120mV	<10mV, 0.01mV	>10mV, ±0.1% F.S.
Ohm	0~400	<50 , 0.05	>50 , ±0.1% F.S.

Compensation accuracy: 1°C (Temperature compensation range:  
-40°C ~ +85°C)

Temperature drift: 25ppm/°C

Response time: 1s

Electromagnetic IEC 61326-1

compatibility:

Dielectric strength: 1500V AC (Input/Output)

Insulation resistance: 100M (Input/Output)

Operation temperature: -40°C ~ +85°C

Storage temperature: -40°C ~ +85°C

Dimension: Ø 44x25.5mm

Wire size: 1.5mm<sup>2</sup>

Screw terminal torque: 0.5Nm

#### Wiring diagram

